

TT-10-RS-1/ TT-10-RS-2 2D Rocker-Shaker

HIGHLIGHTS

- Smooth see-saw rocking motion with fixed angle 10°
- Digital speed control easily adjusts from 5-80 rpm
- Independent digital timer control up to 99 hrs 59 min
- Maximum load up to 5kg
- Maintenance-free, brushless DC motor provides quiet and reliable operation
- Non-slip rubber mat included
- Stainless steel platform for durability and easy



TT-10-RS-1

TT-10-RS-1/TT-10-RS-2 2D Rocker-Shaker provides see-saw rocking action to achieve gentle to intensive mixing of solutions or nutrient media in vessels such as culture flasks, petri dishes etc.

TT-10-RS-2 2D Rocker-Shaker is installed with dual platform doubles work surface without sacrificing bench space.

APPLICATIONS

- Gel staining/destaining after electrophoresis
- Homogenization of bioextraction media
- Biomolecule hybridization
- Washing blots
- Antibody staining
- Immunoprecipitations



TT-10-RS-2

TECHNICAL DATA

Specifications	TT-10-RS-1 2D Rocker-Shaker	TT-10-RS-2 2D Rocker-Shaker
Speed range	5-80 rpm	5-80 rpm
Rocking motion	See-saw	See-saw
Fixed tilt angle	10° / 25 mm (up & down)	10° / 25 mm (up & down)
Digital time setting	1 min - 99h 59 min or continuous	1 min - 99h 59 min or continuous
Maximum load	5.0 kg	5.0 kg
Platform with non-slip rubber mat supplied as standard	One-level platform with flat non-slip rubber mat	Two-level platform with flat non-slip rubber mat
Platform dimension	280 x 228 mm	280 x 228 mm
Overall dimension with platform (WxDxH)	284 x 264 x 134 mm	284 x 264 x 248 mm
Electrical supply	Input AC 100-240V, 50/60 Hz; Output DC 12V	Input AC 100-240V, 50/60 Hz; Output DC 12V
Net weight	5.2 kg	6.0 kg
Permissible ambient temperature	4 - 45°C	4 - 45°C
Permissible relative humidity	≤70%	≤70%

ORDERING INFORMATION

Cat. No.	2D Rocker-Shaker
TT-10-RS-1	2D Rocker-Shaker TT-10-RS-1, One-level flat platform with non-slip rubber mat, AC 100-240V
TT-10-RS-2	2D Rocker-Shaker TT-10-RS-2, Two-level flat platform with non-slip rubber mat, AC 100-240V